

Axle Configuration: Differential Drive with Lockout

Working Gears: 3 forward, 3 reverse

Working Gear Speeds: 0.9, 2.0 and 3.0 MPH

Transport Gear Speed: 9.2 MPH

Standard Wheel/Tire Size: 5x12x22"

Weight: 342 pounds (with 30" tiller)

Individual Wheel (Steering) Brakes: Yes



BCS America Model 853R Two Wheel Tractor - Recoil 8H0CW785

[Read More](#)

SKU:8H0CW785

Price:\$5999

Categories:[BCS America](#)

Product Description

BCS America Model 853R Two-Wheel Tractor - Recoil

One of BCS's most popular models, model 853 is a larger, more fully-featured version of the 732.

The four-speed transmission includes three working speeds in both directions, with the third gear being particularly helpful when mowing large areas. Fourth gear is strictly a transport speed enabling you to drive the BCS Utility Trailer down the lane at speeds up to 9+ miles per hour!

Designed to better accommodate larger, heavier attachments, such as the 32" Brush Mower and 35" Flail Mower, the 853 includes an individual brake for each wheel, making it easier to turn and maneuver. To power larger attachments, the engine size is increased to Honda's GX390 engine. And, with a longer transmission, the standard tire size for the 853 is increased to 22" in diameter; a real plus when navigating uneven terrain and straddling raised beds.

Like all Professional Series models, the 853 features the ease and convenience of Differential Drive. When traction to the wheels is needed, a flip of the lever locks out the differential feature and provides positive pulling/pushing power to both wheels.

Add to these features -- a shuttle-style forward/reverse, BCS's advanced handlebar system with instant access to seven vertical and three horizontal positions, and optional electric start - it's easy to see why the Model 853 is so popular, particularly among rural property owners.

FEATURES

- Differential Drive with On-demand Differential Lockout
- All Gear Drive w/ Heat-treated Steel Gears & Embedded Ball Bearings
- Double Cone Clutch
- Best Warranty in the Industry
- Limited Lifetime Transmission Warranty*
- 3-year Engine Warranty
- Convenient Shuttle-style Forward/Reverse Control
- Easily Adjusted Anti-Vibration Handlebars w/ 180° Rotation
- 7 Vertical Handlebar Settings (front & rear)
- 3 Horizontal Handlebar Settings (front & rear)
- Three Working Speeds in Each Direction
- Transport Speed (rear-mount only)
- 22" Tires
- Individual Wheel Brakes
- Available with Recoil Start or Electric Start (w/ Recoil backup)

SPECS

Engine: Honda GX390

Electric Start Option: Yes

Transmission: All Gear Drive

Clutch Type: Double Cone, Spring-Loaded